

HIGH SPEED DOOR

Cold Storage Rapid Roll-Up Doors

Key Features :

- Rapid operation reduces cold air loss
- Thermal insulation for energy efficiency
- Optional integration with cold room interlocks.
- This cold storage zipper door is rated for temperatures as low as -20°C



PVC Fabric

Insulated PVC sandwich fabric: double skin is 1.2 mm PVC fabric, and inside is filled with high-density insulating rock wool, total thickness is 10mm

Overhead Box & Motor Cover (Optional)

- Galvanized
- Stainless



Safety System Options

- Eye Photocell Reflected
- Beam Photocell
- Gate Photocell
- Beam Photocell - Radar
- Cabled Pneumatic Photocell
- Cabled Optic Sensor
- Photocell with Battery

Bottom Edge

- Soft bottom edge, filled with sand et c.
- Self repairing feature without suffering damage in case of crash

POM/Nylon Zippers

Polyethylene side tracks



Aluminum Side Guides (standard)

- Aluminum extruded
- Elegant outlook
- Hidden screwing with Led seal
- Hidden photocell channel
- Hidden cabling channel
- Double sealing option with rubber seal and brush seal
- Easy to install with "Easy Click" system made of 2-piece as frame and cover

Heater (Optional)

- Anti-condensation solution at the side guides and overhead box.

! The heating solution at the threshold should be considered at the concreting phase.